


02 Sägen und Oszillieren

Farbcodierung				
Material			Fe	Al
empfohlene Drehzahlstufe	3-6	3-5	2-4	3-6

Standard-Sägeblatt

	Durchmesser	Schnittbreite	Bohrungs-Ø	Zähnezahl	Spanwinkel	Zahnform	UVP €*	Bestell-Nr.
	160x1,8x20 W18	160 mm	1,8 mm	20 mm	18	25 °	W 38,00 45,22	500458
	160x2,2x20 W18	160 mm	2,2 mm	20 mm	18	25 °	W 41,30 49,15	768129
	210x2,6x30 W18	210 mm	2,6 mm	30 mm	18	20 °	W 63,10 75,09	493197
	230x2,5x30 W24	230 mm	2,5 mm	30 mm	24	20 °	W 79,20 94,25	500647
	350x3,5x30 W24	350 mm	3,5 mm	30 mm	24	10 °	W 94,00 111,86	769667


Panther-Sägeblatt

	160x1,8x20 PW12	160 mm	1,8 mm	20 mm	12	25 °	W 52,10 62,00	500460
	160x2,2x20 PW12	160 mm	2,2 mm	20 mm	12	20 °	PW 56,00 66,64	496301
	190x2,6 FF PW16	190 mm	2,6 mm	FF**	16	28 °	PW 71,80 85,44	492049
	210x2,6x30 PW16	210 mm	2,6 mm	30 mm	16	28 °	PW 79,90 95,08	493196
	225x2,6x30 PW18	225 mm	2,6 mm	30 mm	18	28 °	PW 80,20 95,44	496303
	230x2,5x30 PW18	230 mm	2,5 mm	30 mm	18	28 °	PW 77,00 91,63	500646
	254x2,4x30 PW24	254 mm	2,4 mm	30 mm	24	20 °	PW Verfügbar ab Sommer 2020	575974

Universal-Sägeblatt

	160x2,2x20 W28	160 mm	2,2 mm	20 mm	28	15 °	W 64,10 76,28	496302
	190x2,6 FF W32	190 mm	2,6 mm	FF**	32	10 °	W 80,00 95,20	492048
	210x2,4x30 W36	210 mm	2,4 mm	30 mm	36	15 °	W 82,40 98,06	493198
	216x2,3x30 W36	216 mm	2,3 mm	30 mm	36	-5 °	W 95,40 113,53	500124
	225x2,6x30 W32	225 mm	2,6 mm	30 mm	32	20 °	W 80,20 95,44	488288
	254x2,4x30 W40	254 mm	2,4 mm	30 mm	40	15 °	W Verfügbar ab Sommer 2020	575975
	260x2,5x30 W60	260 mm	2,5 mm	30 mm	60	-5 °	W 152,90 181,95	494604

Feinzahn-Sägeblatt

	160x1,8x20 W32	160 mm	1,8 mm	20 mm	32	5 °	W 62,90 74,85	500459
	160x2,2x20 W48	160 mm	2,2 mm	20 mm	48	5 °	W 79,80 94,96	491952
	190x2,4 FF W48	190 mm	2,4 mm	FF**	48	8 °	W 95,90 114,12	492050
	210x2,4x30 W52	210 mm	2,4 mm	30 mm	52	5 °	W 111,80 133,04	493199
	216x2,3x30 W48	216 mm	2,3 mm	30 mm	48	-5 °	W 116,30 138,40	491050
	216x2,3x30 W60	216 mm	2,3 mm	30 mm	60	-5 °	W 139,20 165,65	500125
	225x2,6x30 W48	225 mm	2,6 mm	30 mm	48	10 °	W 112,30 133,64	488289
	230x2,5x30 W48	230 mm	2,5 mm	30 mm	48	10 °	W 108,40 129,00	500648
	254x2,4x30 W60	254 mm	2,4 mm	30 mm	60	10 °	W Verfügbar ab Sommer 2020	575976
	260x2,5x30 W80	260 mm	2,5 mm	30 mm	80	-5 °	W 183,40 218,25	494605

empfohlene Drehzahlstufe

Zu bearbeitendes Material

Passend für Maschine

☒ sehr gut
☐ geeignet